

一般用メートルねじ JIS B 0205-2:2001 (ISO 261:1998)

No1 M1～M39

単位:mm

呼び径D,d			並目	ピッチP									
1種	2種	3種		細目									
第1 選択	第2 選択	第3 選択		3	2	1.5	1.25	1	0.75	0.5	0.35	0.25	0.2
1	-	-	0.25										0.2
-	1.1	-	0.25										0.2
1.2	-	-	0.25										0.2
-	1.4	-	0.3										0.2
1.6	-	-	0.35										0.2
-	1.8	-	0.35										0.2
2	-	-	0.4									0.25	
-	2.2	-	0.45									0.25	
2.5	-	-	0.45								0.35		
3	-	-	0.5								0.35		
-	3.5	-	0.6								0.35		
4	-	-	0.7								0.5		
-	4.5	-	0.75								0.5		
5	-	-	0.8								0.5		
-	-	5.5									0.5		
6	-	-	1							0.75			
-	7	-	1							0.75			
8	-	-	1.25					1		0.75			
-	-	9	1.25					1		0.75			
10	-	-	1.5				1.25	1		0.75			
-	-	11	1.5					1		0.75			
12	-	-	1.75				1.5	1.25	1				
-	14	-	2				1.5	1.25(1)	1				
-	-	15					1.5		1				
16	-	-	2				1.5		1				
-	-	17					1.5		1				
-	18	-	2.5			2	1.5		1				
20	-	-	2.5			2	1.5		1				
-	22	-	2.5			2	1.5						
24	-	-	3			2	1.5		1				
-	-	25				2	1.5		1				
-	-	26					1.5		1				
-	27	-	3			2	1.5						
-	-	28				2	1.5						
30	-	-	3.5	(3)	2	1.5							
-	-	32			2	1.5							
-	33	-	3.5	(3)	2	1.5							
-	-	35(2)				1.5							
36	-	-	4		3	2	1.5						
-	-	38					1.5						
-	39	-	4		3	2	1.5						

注(1) 内燃機関用点火プラグのねじに限って用いることができる。

(2) 転がり軸受を固定するねじに限って用いることができる。