

一般用メートルねじ JIS B 0205-2:2001 (ISO 261:1998)

No2 M40~M185

単位: mm

呼び径D,d			並目	ピッチP					
1種 第1 選択	2種 第2 選択	3種 第3 選択		細目					
				8	6	4	3	2	1.5
-	-	40					3	2	1.5
42	-	-	4.5			4	3	2	1.5
-	45	-	4.5			4	3	2	1.5
48	-	-	5			4	3	2	1.5
-	-	50					3	2	1.5
-	52	-	5			4	3	2	1.5
-	-	55				4	3	2	1.5
56	-	-	5.5			4	3	2	1.5
-	-	58				4	3	2	1.5
-	60	-	5.5			4	3	2	1.5
-	-	62				4	3	2	1.5
64	-	-	6			4	3	2	1.5
-	-	65				4	3	2	1.5
-	68	-	6			4	3	2	1.5
-	-	70			6	4	3	2	1.5
72	-	-			6	4	3	2	1.5
-	-	75			6	4	3	2	1.5
-	76	-			6	4	3	2	1.5
-	-	78						2	
80	-	-			6	4	3	2	1.5
-	-	82						2	
-	85	-			6	4	3	2	
90	-	-			6	4	3	2	
-	95	-			6	4	3	2	
100	-	-			6	4	3	2	
-	105	-			6	4	3	2	
110	-	-			6	4	3	2	
-	115	-			6	4	3	2	
-	120	-			6	4	3	2	
125	-	-		8	6	4	3	2	
-	130	-		8	6	4	3	2	
-	-	135			6	4	3	2	
140	-	-		8	6	4	3	2	
-	-	145			6	4	3	2	
-	150	-		8	6	4	3	2	
-	-	155			6	4	3		
160	-	-		8	6	4	3		
-	-	165			6	4	3		
-	170	-		8	6	4	3		
-	-	175			6	4	3		
180	-	-		8	6	4	3		
-	-	185			6	4	3		